



INDUCTION HOB & WOK (Table Top Series)



CLASSIC TABLE TOP INDUCTION HOB & WOK

Standard Features:

- Automatic safety shut-off
- Material compatibility and small object detection
- Overheating protection
- Compact size and easy to install



Model ▶	TT-2500	TT-2800EM	TT-5000N	TTW-2500	TTW-5000N
Dimension (W x D x H mm)	328 x 422 x 110	295 x 425 x 84	385 x 520 x 197	385 x 485 x 160	385 x 520 x 243
Ceramic glass dimension (mm)	273 x 273 x 4 (thk.)	294 x 275 x 4 (thk.)	300 x 300 x 6 (thk.)	Ø311 x 6 (thk.)	Ø311 x 6 (thk.)
Voltage (V/Ph/Hz)	220~230/1/50~60	220~230/1/50~60	380~400/3+N/50~60	220~230/1/50~60	380~400/3+N/50~60
Power (kW)	2.5	2.8	5.0	2.5	5.0
Amps (A)	12	13 / 15	7.6	12	7.6
Net / Gross weight (kg)	6 / 8	7 / 7.35	18 / 20	9 / 11	18 / 20
CE approval	Yes	Yes	Yes	Yes	Yes

D SERIES TABLE TOP INDUCTION HOB & WOK

New Features:

- IR & NTC dual-sensor for precise temperature control
- 12 power level control
- Safety lock & automatic shut-off
- Removable air filter (washable)



Model ▶	TT-3500D	TTD-3500D	TTW-3500D
Dimension (W x D x H mm)	328 x 475 x 110	400 x 740 x 196	385 x 480 x 160
Ceramic glass dimension (mm)	273 x 273 x 4 (thk.)	350 x 550 x 6 (thk.)	Ø311 x 6 (thk.)
Voltage (V/Ph/Hz)	220~230/1/50~60	380~400/2+N/50~60	220~230/1/50~60
Power (kW)	3.5	3.5 x 2	3.5
Amps (A)	16	16	16
Net / Gross weight (kg)	13 / 15	26 / 28	13 / 15
CE approval	Yes	Yes	Yes

DT SERIES TABLE TOP INDUCTION HOB

New Features:

- Touch temperature control
- Low temperature cooking available with 24-hour timer and temperature setting range from 40°C to 220°C
- IR & NTC dual-sensor for precise temperature control
- 12 power level control
- 1-watt energy saving standby-mode
- Safety lock & automatic shut-off
- Removable air filter (washable)
- One piece integrated PCB board for easy servicing
- Optional accessories include RF wireless food temperature measurement probe



Optional accessories:

RF Wireless Temperature Probe measuring food core temperature



Model ▶	DT-28T	DT-35T
Dimension (W x D x H mm)	328 x 475 x 110	328 x 475 x 110
Ceramic glass dimension (mm)	273 x 273 x 4 (thk.)	273 x 273 x 4 (thk.)
Voltage (V/Ph/Hz)	220~230/1/50~60	220~230/1/50~60
Power (kW)	2.8	3.5
Amps (A)	13	16
Net / Gross weight (kg)	13 / 15	13 / 15
CE approval	Yes	Yes